


Sensor-switched indoor light

RS PRO Connect R10

Neutral white

EAN 4007841057046



Function description

Round. And impressive all round. Connected lighting is as easy as this! The digital RS PRO Connect R10 sensor-switched light is wirelessly adjusted via Bluetooth and app. 4 lighting functions: basic light level, backlight, dimmable main light and emergency light. High-precision HF sensor for reliable detection (10 m reach). The opal diffuser shade provides an even distribution of light. Output 9 W with 1130 lm and 4000 K \varnothing 300 x 55 mm.

Technical specifications

Dimensions (\varnothing x H)	300 x 55,2 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	High frequency
Transmitter power	< 1 mW
Output	9 W
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Luminous flux	1130 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	70000 h
Drop in luminous flux in accordance with LM80	L80B10
Base	without
LED cooling system	Passive Thermo Control

Sensor-switched indoor light

RS PRO Connect R10

Neutral white

EAN 4007841057046

Technical specifications

With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Capability of masking out individual segments	Yes
Electronic scalability	Yes
Mechanical scalability	No
Reach, tangential	Ø 10 m (79 m ²)
Main light adjustable	10 - 100 %
Continuous light	selectable
Twilight setting	2 – 2000 lx
Time setting	5 sec – 30 min
Basic light level function	Yes
Basic light level function, detail	LED effect light
Basic light level function time	10-30 min, all day, all night
Basic light level function percentage, from	20 %
Basic light level function percentage, up to	50 %
Functions	Group parameterisation, Master/slave override, Neighbouring-light function, Presence function
Soft light start	Yes
Impact resistance	IK07
IP rating	IP40
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	PC, opal
Manufacturer's Warranty	5 years
Settings via	Bluetooth
With remote control	No
Version	Neutral white
PU1, EAN	4007841057046

Data sheet



Sensor-switched indoor light

RS PRO Connect R10

Neutral white

EAN 4007841057046

Mood image

